


Existing Note Cell I1.13

Alternate Concrete Wearing Surface	
Type of Concrete Wearing Surface	Type Used (✓)
Low Slump Concrete Wearing Surface	
Silica Fume Concrete Wearing Surface	

MoDOT construction personnel will complete column labeled "Type Used (✓)".

The contractor shall select one of the alternate concrete wearing surfaces listed in the table. The alternate concrete wearing surface method of measurement and basis of payment shall be in accordance with Sec 505.



Revised Note Cell I1.13

Optional Concrete Wearing Surface	
Type of Concrete Wearing Surface	Type Used (✓)
Low Slump Concrete Wearing Surface	
Latex Modified Concrete Wearing Surface	
Silica Fume Concrete Wearing Surface	

MoDOT construction personnel will complete column labeled "Type Used (✓)".

The contractor shall select one of the alternate concrete wearing surfaces listed in the table. The alternate concrete wearing surface method of measurement and basis of payment shall be in accordance with Sec 505.

Optional Very Early Strength Concrete Wearing Surface	
Type of Concrete Wearing Surface	Type Used (✓)
Latex Modified Very Early Strength Concrete Wearing Surface	
CSA Cement Very Early Strength Concrete Wearing Surface	

MoDOT construction personnel will complete column labeled "Type Used (✓)".

The contractor shall select one of the optional very early strength concrete wearing surfaces listed in the table. The optional very early strength concrete wearing surface method of measurement and basis of payment shall be in accordance with Sec 505.

Detailing Guidance  
(Do not show on plans)  
Use appropriate table and modify options as specified on the Bridge Memorandum.

Existing Note Cell B3.50


Alternate Asphaltic Concrete Wearing Surface	
Type of Wearing Surface with Asphalt Binder Type	Mix Used (✓)
SP125BSM Mix with PG 76-22	
SP125BLP Mix with PG 76-22	
SP125BSM Mix with PG 70-22	
SP125CLP Mix with PG 70-22	

MoDOT construction personnel shall complete column labeled "Mix Used (✓)".

The contractor shall select one of the alternate asphaltic concrete wearing surfaces listed in the table. The mixture shall be in accordance with Sec 403 and produced in accordance with Sec 404.

The area of the asphaltic concrete wearing surface will be measured and computed to the nearest square yard. This area will be measured transversely from out to out of overlay and longitudinally from end of slab to end of slab.

Payment for alternate Asphaltic Concrete Wearing Surface will be considered completely covered by the contract unit price per square yard.



Revised Note Cell B3.50

Optional Asphaltic Concrete Wearing Surface	
Type of Wearing Surface with Asphalt Binder Type	Mix Used (✓)
SP125BSM Mix with PG 76-22	
SP125BLP Mix with PG 76-22	
SP125BSM Mix with PG 70-22	
SP125CLP Mix with PG 70-22	

MoDOT construction personnel shall complete column labeled "Mix Used (✓)".

The contractor shall select one of the optional asphaltic concrete wearing surfaces listed in the table. The mixture shall be in accordance with Sec 403 and produced in accordance with Sec 404.

The area of the asphaltic concrete wearing surface will be measured and computed to the nearest square yard. This area will be measured transversely from out to out of wearing surface and longitudinally from end of slab to end of slab.

Payment for Optional Asphaltic Concrete Wearing Surface will be considered completely covered by the contract unit price per square yard.

New Note Cell I1.14

Optional Polymer Wearing Surface	
Type of Polymer Wearing Surface	Type Used (✓)
Epoxy Polymer Wearing Surface	
MMA Polymer Slurry Wearing Surface	

MoDOT construction personnel will complete column labeled "Type Used (✓)".

The contractor shall select one of the optional polymer concrete wearing surfaces listed in the table. The optional polymer concrete wearing surface method of measurement and basis of payment shall be in accordance with Sec 623.

New Note Cell B3.60

Optional Ultrathin Bonded Asphalt Wearing Surface	
Type of Wearing Surface	Mix Used (✓)
Type A	
Type B	
Type C	

MoDOT construction personnel will complete column labeled "Mix Used (✓)".

The contractor shall select one of the optional ultrathin bonded asphalt wearing surfaces listed in the table.