

Design Standards Letter

Letter Number: G-1965-25

Letter Date: 06/09/1965

Effective Date: 07/01/1965

Section/Plan No.: None

Subject: Special Provisions (New and Revised)

Body

ALL DIVISION, DISTRICT AND URBAN ENGINEERS AND CHIEF COUNSEL:

We are transmitting under separate cover, several copies of the following new or revised special provisions:

Paved Approaches (July 1965). This is a new special provision clarifying the payment for integral curb constructed on paved approaches. Curb is not a separate pay item, but is included in the price bid for paved approaches, per square yard.

Erosion Control - Seeding - Mulching (Front Feb. 1, 1965 - Back July, 1965). This special provision has been revised to include information on leguminous seeds and their inoculation.

Asphaltic Concrete Pavement (July, 1965). This special provision has been revised to clarify a grammatically correct, but widely misinterpreted statement concerning the roller and density requirements for shoulders adjacent to rigid pavements and resurfaced rigid pavements in Section 43.4.5.2.1

Class X Concrete (June, 1965). This is a new special provision correcting the reference to "Section 51" to read "Section 53" in Section 47.11.1 of the specifications. This correction has previously been written special for each project, and is now standard. In addition, a revision of the slump has been made, and the moisture sensing device deleted, for the fine aggregate bin or weighing hopper. This special provision is effective with the June, 1965 Letting, and will be called for by the Bridge Division for applicable projects.

Pedestrian Interval Timing Unit (July, 1965). This special provision has been revised to delete the statement "If right arrow indications are used, such indications for vehicular turns conflicting with the pedestrian movement shall not be shown during the timing of the pedestrian minimum and clearance intervals."

Aggregate - Aggregate Base (July, 1965). This special provision has been revised to permit testing for density on aggregate base placed on open graded material to be made on the

combined lifts, if satisfactory density cannot be obtained on the first lift.

Except as noted above, these special provisions will be effective with the July, 1965 Letting.

L. V. McLaughlin
Engineer Of Surveys and Plans