

Design Standards Letter

Letter Number: G-1966-08

Letter Date: 02/18/1966

Effective Date: 05/27/1966

Section/Plan No.: None

Subject: Revised Special Provisions and Standard Drawing

Body

ALL DIVISION AND DISTRICT ENGINEERS AND CHIEF COUNSEL:

We are furnishing you herewith several copies of the following revised special provisions and standard drawing.

Property Fence. This special provision has been revised to modify the requirements for aluminum alloy coating on aluminum coated steel fabric and to permit the use of aluminum alloy wire ties in addition to the zinc-coated steel wire or aluminum-coated steel wire for ties to be used in conjunction with zinc-coated steel fabric or with aluminum-coated steel fabric. This special provision will be used where applicable beginning with the April 29, 1966 Letting.

Class A Underdrains. This special provision has been revised to permit perforations to be located on one of the neutral axes of all corrugations and to permit the use of 5/16 inch diameter bolts for the coupling bands. This special provision will be used where applicable beginning with the April 29, 1966 Letting.

Standard Drawing 21.55. This drawing has been revised to delete references to guard posts for commercial entrance delineation. The Design Manual Section 14.3.16.1.3.1 covering Commercial Entrances will be revised in the near future to the effect that "Type S Curb is specified for the delineation of commercial entrances and along the right-of-way line as necessary to restrict use of right-of-way area as indicated by the Division of Maintenance and Traffic Standard Driveway Plans or Standard Drawing 21.55." This revision is to be effective with the May 27, 1966 letting, and all plans should be revised accordingly.

L. V. McLaughlin
Division Engineer
Surveys and Plans