

Design Standards Letter

Letter Number: G-1966-29

Letter Date: 08/22/1966

Effective Date: 10/27/1966

Section/Plan No.: None

Subject: Revised Special Provision and Standard Drawing

Body

ALL DIVISION AND DISTRICT ENGINEERS AND CHIEF COUNSEL:

We are furnishing you herewith several copies of the special provision and standard drawing as follows:

Bearing Pile. This special provision was furnished you by General Letter No. 27, 1966. Subsequent to that transmittal, it was deemed advisable to clarify payment for the piles. As a result, Section 52.6.8 and Section 52.6.9 on page four of this special have been revised. Please note that this revision carries the same date as that of the previous transmittal, and the attached page will be used for the September 30, 1966 Letting.

Standard Drawing 86.00. This drawing has been revised to indicate that the face of the guard rail beam is at the shoulder line when used along six-foot ramp shoulders. A note, reducing the normal 2' 0" to zero, has been added to the Plan and Elevation of the Type A and Type C guard rail for such installations. In addition, Plan C has been added to the typical installations at structures for use on multi-lane pavements with separate structures where the roadway has four-foot inside shoulders. This revision of the drawing will be used where applicable, beginning with the October 27, 1966 Letting.

L.V. McLaughlin
Division Engineer
Surveys and Plans