

Design Standards Letter

Letter Number: G-1967-36

Letter Date: 11/15/1967

Effective Date: 01/19/1968

Section/Plan No.: None

Subject: Revised Standard Drawings and Special Provisions

Body

ALL DIVISION AND DISTRICT ENGINEERS AND CHIEF COUNSELS:

We are furnishing you herewith several copies of the following revised standard drawings and special provisions.

Drawing 54.00. This drawing has been revised to correct the shape of the curb in several locations and to remove entirely the upper left drawing showing reinforcement where the top layer of reinforcing steel is parallel to the centerline of the roadway. This drawing will be included where applicable, beginning with the December 14, 1967 letting.

Drawing 72.03 (Sheet 1 of 6). This drawing has been revised to change the hinge plate thickness (t3) for post designs No. 2, 5, 6, 7 and 8. Also, general notes No. 10, 11, 12, and 13 have been added pertaining to field tightening of nuts. This drawing will be included where applicable beginning with the January 19, 1968 Letting.

Removal of Existing Structures and Miscellaneous Facilities. This special provision has been revised to delete Section 24.1.4 pertaining to removal and resetting of mail boxes, signs, or markers. Such removal and resetting is now covered, in a modified form, in the special provision on Scope of Work and Control of Work hereinafter described. This special will be included where applicable beginning with the January 19, 1968 Letting

Scope of Work and Control of Work. This special has been revised to require the contractor to remove mail boxes, signs, or markers, but only to reset mail boxes. This special will be included in all contracts beginning with the January 19, 1968 Letting.

Plant Mix Bituminous Stabilized Base. Page 1, Section 41.22.2.1 has been revised to delete the first sentence with no substitution. This special will be included where applicable beginning with the January 19, 1968 Letting.

L. V. McLaughlin
Division Engineer
Surveys and Plans