

# Design Standards Letter

**Letter Number: G-1972-12**

**Letter Date: 11/10/1972**

**Effective Date: 01/01/1973**

**Section/Plan No.: P203.40, P502.00, P606.00, P617.00, P903.03**

**Subject: Revised Standard Drawings**

## Body

-----  
ALL DIVISION AND DISTRICT ENGINEERS

Attached are copies of revised Standard Drawings numbered 203.40B, 502.00D, 606.00C, 617.00G and 903.03L.

Drawing 203.40B. Shoulder widths on auxiliary lanes adjacent to the throughway is shown as a minimum of 6 feet, and a note has been added to see typical sections for ramp shoulder widths.

Drawing 502.00D. On Plan for Locating Joints, the taper of the auxiliary lanes leaving or entering the throughway may be omitted to the 2-foot dimension from the throughway pavement edge.

Drawing 606.00C. On Sheet 1 of 2 on the elevation view, Reflectorized White has been added to the Striping Note.

Drawing 617.00G. On Sheet 2 of 2, Transition Details at Piers, Section B, the dimensions have been deleted and a Note has been added to See Section A for Dimensions.

Drawing 903.03L. On Sheet 5 of 6, Post Clamps, Detail D, a dimension of 1-3/4 inches for Clamp Bolt Spacing has been added.

The above revised Standard Drawings will be effective with the January, 1973 Letting.

James F. Roberts  
Division Engineer  
Surveys and Plans