

Design Standards Letter

Letter Number: **G-1992-19**

Letter Date: **10/19/1992**

Effective Date: **11/01/1992**

Section/Plan No.: **None**

Subject: **Job Special Provisions**

Body

Beginning with the November 1992 letting, add the following paragraph to all Traffic Control Plan Special Provisions for routes with an ADT for 5000 or more.

"Except for normal construction activities, the contractor shall not park vehicles or store equipment or materials closer than 30 feet to the edge of pavement carrying traffic, unless the equipment, vehicles, or materials are located in a properly protected area or an off-site storage area."

For other lower volume routes with less than 5000 ADT, the distance may vary to meet clear zone requirements less than 30 feet. The clear zone distance for this special provision will need to be furnished by the District when plans are submitted to headquarters office.

The following paragraph will be added to all Traffic Control Plan Special Provisions for routes with an ADT of less than 5000 where the clear zone requirements are not designated and the roadway foreslope or fill slope is steeper than 4 to 1.

"Except for normal construction activities, the contractor shall not park vehicles or store equipment or materials closer to the edge of pavement carrying traffic than the toe of the roadway foreslope or fill slope, unless the equipment, vehicles or materials are located in a properly protected area."

The special provisions will not be required for maintenance leveling contracts.

do/kd