

Design Standards Letter

Letter Number: P-1990-03

Letter Date: 08/13/1990

Effective Date: 08/13/1990

Section/Plan No.: P606.22, P606.23, P616.10, P617.00, P731.10, P902.40, P902.50, P903.03

Subject: Revised Drawings

Body

Enclosed are copies of revised standard plans which are effective with the September 1990 letting.

606.22H: Dimensions removed from section A-A. Drawing revised to show three beam rails on the outside of the terminal connector.

606.23A: The first post off the structure has been removed.

616.10M: 1 of 3: Portion of note for portable sign mounting deleted. Misspelled words corrected.

2 of 2: Revised Flashing Arrow Panel and notes. Revised Speed Limit Assembly and notes. Revised Section A-A for Temporary Asphalt Island.

3 of 3: W020-7b revised to a symbol sign. W020-7x plaque added. W020-8 deleted. @022-5 added. R3-1b, R3-2b, and R30-4b revised to symbol signs. R20-1 revised to S4-4a. Other spelling and sign number designation changes.

617.00W: 1 of 3: Allowable tolerances note added.

2 of 3 and 3 of 3: No revisions.

731.10J: 1 of 4: No revisions.

2 of 4: Type B and Type C inlets shifted 3 inches from median barrier to permit inlet grade removal.

3 of 4 and 4 of 4: No revisions.

902.40J: Reference to standard hex nut deleted.

902.50F: Wire size to controller revised. 6' x 6' loop added.

903.03AN: 1 of 5: Post stub elevation revised to 4-inch maximum. Bolt torque requirements revised. Bolt retainer added. Single post, design 3, weight per foot revised.

2 of 5: Post stub elevation revised to 4-inch maximum. Bolt torque requirements revised. Bolt retainer added to single direction slip base.

3 of 5 and 4 of 5: No revisions.

5 of 5: Flexible delineator embedment depths clarified. Note corrected for Type IV Object Marker.

D02: Standard plan index revised to reflect foregoing changes.

jdp/kd

Enclosure